

Package ‘MPBoost’

October 6, 2019

Type Package

Title Treatment Allocation in Clinical Trials by the Maximal Procedure

Version 0.1-3

Date 2019-10-02

Author Ignacio López-de-Ullibarri [aut, cre]

Maintainer Ignacio López-de-Ullibarri <ignacio.lopezdeullibarri@udc.es>

Description Performs treatment allocation in two-arm clinical trials by the maximal procedure described by Berger et al. (2003) <doi:10.1002/sim.1538>. To that end, the algorithm provided by Salama et al. (2008) <doi:10.1002/sim.3014> is implemented.

License GPL (>= 2)

Imports Rcpp (>= 1.0.1)

LinkingTo Rcpp, BH

Depends R (>= 3.6.0)

Suggests knitr, pinp, rmarkdown

VignetteBuilder knitr

NeedsCompilation yes

Encoding UTF-8

Repository CRAN

Date/Publication 2019-10-06 12:50:08 UTC

R topics documented:

MPBoost-package	2
mpboost	2

Index	4
--------------	----------

 MPBoost-package

Treatment Allocation in Clinical Trials by the Maximal Procedure

Description

Performs treatment allocation in two-arm clinical trials by the maximal procedure described by Berger et al. (2003) <doi:10.1002/sim.1538>. To that end, the algorithm provided by Salama et al. (2008) <doi:10.1002/sim.3014> is implemented.

Details

Index of help topics:

MPBoost-package	Treatment Allocation in Clinical Trials by the Maximal Procedure
mpboost	Compute Allocation Sequences by the Maximal Procedure

Author(s)

Ignacio López-de-Ullibarri

Maintainer: Ignacio López-de-Ullibarri <ignacio.lopezdeullibarri@udc.es>

References

Berger, V. W., Ivanova, A., Knoll, M. D. (2003). Minimizing predictability while retaining balance through the use of less restrictive randomization procedures. *Statistics in Medicine*, 22: 3017-3028. <https://doi.org/10.1002/sim.1538>.

Salama, I., Ivanova, A., Qaqish, B. (2008). Efficient generation of constrained block allocation sequences. *Statistics in Medicine*, 27, 1421-1428. <https://doi.org/10.1002/sim.3014>.

 mpboost

Compute Allocation Sequences by the Maximal Procedure

Description

This function produces a treatment assignment sequence generated according to the maximal procedure of Berger et al. (2003). It is an implementation of the algorithm proposed by Salama et al. (2008).

Usage

```
mpboost(N1, N2, MTI = 2L)
```

Arguments

N1	An integer specifying the size of the sample assigned to treatment 1.
N2	An integer specifying the size of the sample assigned to treatment 2.
MTI	An integer specifying the maximum tolerated imbalance (MTI). The default is 2.

Value

A vector of N1 1's and N2 2's representing the allocation sequence.

Note

See the package's vignette for more details and further examples of the use of the function.

References

- Berger, V. W., Ivanova, A., Knoll, M. D. (2003). Minimizing predictability while retaining balance through the use of less restrictive randomization procedures. *Statistics in Medicine*, 22: 3017-3028. <https://doi.org/10.1002/sim.1538>.
- Salama, I., Ivanova, A., Qaqish, B. (2008). Efficient generation of constrained block allocation sequences. *Statistics in Medicine*, 27, 1421-1428. <https://doi.org/10.1002/sim.3014>.

Examples

```
#\donttest{  
mpboost(N1 = 25, N2 = 25, MTI = 3)  
#}
```

Index

*Topic **clinical trial**

mpboost, [2](#)

*Topic **constrained block
randomization**

mpboost, [2](#)

*Topic **package**

MPBoost-package, [2](#)

MPBoost (MPBoost-package), [2](#)

mpboost, [2](#)

MPBoost-package, [2](#)