

ICIGWAS

Efficient Estimation of Discrete-Time Multivariate Frailty Model
Using Exact Likelihood Function for Grouped Survival Data

2017-02-20

Introduction

- ▶ This document provides an example for using the `lc1GWAS` package to estimate the baseline hazard, frailty variance, and fixed effect parameter for a discrete-time frailty model with random effects using the exact likelihood. The functions are designed to analyze grouped time-to-event data accounting for family structure of related individuals (i.e., trios).
- ▶ The major algorithms in this package are written in C++, which is ported to R by `Rcpp`, to facilitate fast computation.

Model Assumptions

- ▶ The input data is assumed to be organized such that records for each family occur consecutively, and that records for offspring precede those for parents. The variance matrix for the random effects is assumed to be of the form $\text{var}*\mathbf{K}$, where \mathbf{K} is a matrix of kinship coefficients between family members.
- ▶ The following family groupings are permitted: (Individual), (Offspring, Offspring), (Offspring, Parent), (Offspring, Parent, Parent), and (Offspring, Offspring, Parent, Parent). Other family structures have not been implemented.

betaEst

```
beta <- betaEst(fam_group, alpha, dtime, delta,  
               g, var, lower = 0, upper = 2)
```

Function arguments:

- `fam_group`: Vector of family indicators for each sample.
- `alpha`: Vector of baseline survival rates for each time interval.
- `dtime`: Vector of observed discrete survival times for each sample.
- `delta`: Event indicator vector: 1 indicates observed event, 0 indicates censored.
- `g`: Vector of numeric genotypes for each sample.
- `var`: Scalar for frailty variance.
- `lower`: Scalar for the lower bound of the fixed effect parameter estimation search region.
- `upper`: Scalar for the upper bound of the fixed effect parameter estimation search region.

Returned Value of betaEst

Function returns:

betaEst: Scalar estimate of the fixed effect parameter.

varEst

```
var <- varEst(fam_group, alpha, dtime, delta,  
             g, beta, lower = 0, upper = 2)
```

Function arguments:

- `fam_size`: Vector of family indicators for each sample.
- `alpha`: Vector of baseline survival rates for each time interval.
- `dtime`: Vector of observed discrete survival times for each sample.
- `delta`: Event indicator vector: 1 indicates observed event, 0 indicates censored.
- `g`: Vector of numeric genotypes for each sample.
- `beta`: Scalar for the fixed effect size.
- `lower`: Scalar for the lower bound of the variance estimation search region.
- `upper`: Scalar for the upper bound of the variance estimation search region.

Returned Value of `varEst`

Function returns:

`varEst`: Scalar estimate of the frailty variance.

alphaEst

```
alpha <- alphaEst(dtime, delta)
```

Function arguments:

`dtime`: Vector of observed discrete survival times for each sample.

`delta`: Event indicator vector: 1 indicates observed event, 0 indicates censored.

Function returns:

`alphaEst`: Vector of estimates of the baseline survival rates.

Example

Generate discrete survival data:

```
alphas <- c(0.75, 0.6666667, 0.5, 0.0)
fgrp   <- c(1, 1, 1, 2, 2, 2, 3, 3, 3)
dtimes <- c(1, 3, 3, 4, 1, 1, 2, 3, 1)
deltas <- c(1, 0, 1, 1, 1, 0, 1, 0, 1)
gs     <- c(0, 1, 1, 1, 2, 2, 0, 0, 0)
var    <- 0.2
```

Load `lc1GWAS` (after installing its dependent packages):

```
library(lc1GWAS)
```

Example Execution

An example estimation of β where the nuisance parameters are estimated under the null hypothesis:

Estimate alphas (always under the null hypothesis)

```
alphaest <- alphaEst(dtimes, deltas)$alphaEst
alphaest

## [1] 0.625 0.800 0.500 0.000
```

Estimate variance under the null by setting $\beta = 0$.

```
var <- varEst(fgrp, alphaest, dtimes, deltas, gs, beta = 0, lower = 0, upper = 2)
var$varEst

## [1] 0.763932
```

Estimate β

```
betaEst(fgrp, alphaest, dtimes, deltas, gs, var$varEst, lower = 0, upper = 2)

## $betaEst
## [1] 0.7640378
```

Session Information

- ▶ R Under development (unstable) (2017-02-20 r72220), x86_64-pc-linux-gnu
- ▶ Running under: Debian GNU/Linux 8 (jessie)
- ▶ Matrix products: default
- ▶ BLAS: /usr/lib/openblas-base/libblas.so.3
- ▶ LAPACK: /usr/lib/openblas-base/liblapack.so.3
- ▶ Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- ▶ Other packages: knitr 1.11, lclGWAS 1.0.3
- ▶ Loaded via a namespace (and not attached): Rcpp 0.12.9, compiler 3.4.0, evaluate 0.8, formatR 1.2.1, highr 0.5.1, magrittr 1.5, stringi 1.0-1, stringr 1.0.0, tools 3.4.0

```
## [1] "Start Time Mon Feb 20 16:11:41 2017"  
## [1] "End Time    Mon Feb 20 16:11:43 2017"
```