

Package ‘stmights’

March 29, 2021

Type Package

Title A 'Shiny' Application for Inspecting Structural Topic Models

Version 0.4.1

Date 2021-03-29

URL <https://github.com/cschwem2er/stmights>

BugReports <https://github.com/cschwem2er/stmights/issues>

Description

This app enables interactive validation, interpretation and visualization of structural topic models from the 'stm' package by Roberts and others (2014) <doi:10.1111/ajps.12103>. It also includes helper functions for model diagnostics and extracting data from effect estimates.

Imports stm (>= 1.3.5), tidygraph (>= 1.1.0), ggraph (>= 2.0.0),
igraph (>= 1.2.0), ggrepel (>= 0.8.0), shiny (>= 1.5.0),
shinyBS (>= 0.6.0), shinydashboard (>= 0.7.0), shinyjs (>=
1.0.0), ggplot2 (>= 3.3.0), purrr (>= 0.3.0), stringr (>=
1.4.0), dplyr (>= 1.0.0), tibble (>= 2.1.0), readr (>= 1.3.0),
huge (>= 1.3.0), stats, scales

Suggests quanteda (>= 2.0.0), knitr, rmarkdown

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Carsten Schwemmer [aut, cre] (<<https://orcid.org/0000-0001-9084-946X>>),
Jonne Guyt [ctb]

Maintainer Carsten Schwemmer <c.schwem2er@gmail.com>

Repository CRAN

Date/Publication 2021-03-29 14:10:02 UTC

R topics documented:

get_diag	2
get_effects	3
get_network	5
run_stminsights	6

Index	9
--------------	----------

get_diag	<i>computes stm model diagnostics</i>
----------	---------------------------------------

Description

get_diag() is a helper function to compute average and median [semanticCoherence](#) and [exclusivity](#) for a number of [stm](#) models. The function does not work for models with content covariates.

Usage

```
get_diag(models, outobj)
```

Arguments

models	A list of stm models.
outobj	The out object containing documents for all stm models.

Value

Returns model diagnostics in a data frame.

Examples

```
library(stm)
library(dplyr)
library(ggplot2)
library(quanteda)

# prepare data
data <- corpus(gadarian, text_field = 'open.ended.response')
docvars(data)$text <- as.character(data)
data <- dfm(data, stem = TRUE, remove = stopwords('english'),
            remove_punct = TRUE)
out <- convert(data, to = 'stm')

# fit models
gadarian_3 <- stm(documents = out$documents,
                 vocab = out$vocab,
                 data = out$meta,
                 prevalence = ~ treatment + s(pid_rep),
```

```

      K = 3,
      max.em.its = 1, # reduce computation time for example
      verbose = FALSE)

gadarian_5 <- stm(documents = out$documents,
                 vocab = out$vocab,
                 data = out$meta,
                 prevalence = ~ treatment + s(pid_rep),
                 K = 5,
                 max.em.its = 1, # reduce computation time for example
                 verbose = FALSE)

# get diagnostics
diag <- get_diag(models = list(
  model_3 = gadarian_3,
  model_5 = gadarian_5),
  outobj = out)

## Not run:
# plot diagnostics
diag %>%
  ggplot(aes(x = coherence, y = exclusivity, color = statistic)) +
  geom_text(aes(label = name), nudge_x = 5) + geom_point() +
  labs(x = 'Semantic Coherence', y = 'Exclusivity') + theme_light()

## End(Not run)

```

get_effects

extract stm effect estimates

Description

get_effects() is a helper function to store effect estimates from stm in a data frame.

Usage

```

get_effects(
  estimates,
  variable,
  type,
  ci = 0.95,
  moderator = NULL,
  modval = NULL,
  cov_val1 = NULL,
  cov_val2 = NULL
)

```



```

    get_effects(estimates = prep_int,
                variable = 'pid_rep',
                type = 'continuous',
                moderator = 'treatment',
                modval = 0)
  )

# plot interaction effects
effects_int %>% filter(topic == 2) %>%
  mutate(moderator = as.factor(moderator)) %>%
  ggplot(aes(x = value, y = proportion, color = moderator,
            group = moderator, fill = moderator)) +
  geom_line() +
  geom_ribbon(aes(ymin = lower, ymax = upper), alpha = 0.2) +
  theme_light() + labs(x = 'PID Rep.', y = 'Topic Proportion',
                      color = 'Treatment', group = 'Treatment', fill = 'Treatment')

```

get_network

extract topic correlation network

Description

get_network() is a helper function to extract topic correlation networks as tidygraph objects and add labels and topic proportions.

Arguments

model	The stm model for computing the correlation network.
method	The method for determining edges. Can be either 'simple' or 'huge'.
cutoff	The correlation cutoff criterion for method = 'cutoff'. Defaults to 0.05.
labels	An optional vector of topic labels. Must include a label for each topic of the model.
cutiso	Remove isolated nodes without any edges from the network. Defaults to FALSE.

Value

Returns tidygraph network of topic correlations.

Examples

```

library(stm)
library(ggraph)
library(quanteda)

# prepare data

```

```

data <- corpus(gadarian, text_field = 'open.ended.response')
docvars(data)$text <- as.character(data)
data <- dfm(data, stem = TRUE, remove = stopwords('english'),
            remove_punct = TRUE)
out <- convert(data, to = 'stm')

# fit model
gadarian_10 <- stm(documents = out$documents,
                  vocab = out$vocab,
                  data = out$meta,
                  prevalence = ~ treatment + s(pid_rep),
                  K = 10,
                  max.em.its = 1, # reduce computation time for example
                  verbose = FALSE)

# extract network
stm_corrs <- get_network(model = gadarian_10,
                        method = 'simple',
                        labels = paste('Topic', 1:10),
                        cutoff = 0.001,
                        cutiso = TRUE)

## Not run:
# plot network
ggraph(stm_corrs, layout = 'fr') +
  geom_edge_link(
    aes(edge_width = weight),
    label_colour = '#fc8d62',
    edge_colour = '#377eb8') +
  geom_node_point(size = 4, colour = 'black') +
  geom_node_label(
    aes(label = name, size = props),
    colour = 'black', repel = TRUE, alpha = 0.85) +
  scale_size(range = c(2, 10), labels = scales::percent) +
  labs(size = 'Topic Proportion', edge_width = 'Topic Correlation') +
  scale_edge_width(range = c(1, 3)) +
  theme_graph()

## End(Not run)

```

run_stminsights

launch the stminsights shiny app

Description

run_stminsights launches the app to analyze Structural Topic models. It requires a .RData file with stm objects as illustrated in the example below.

Usage

```
run_stminsights(use_browser = TRUE)
```

Arguments

`use_browser` Choose whether you want to launch the shiny app in your browser. Defaults to TRUE.

Examples

```
## Not run:

library(stm)
library(quanteda)

# prepare data
data <- corpus(gadarian, text_field = 'open.ended.response')
docvars(data)$text <- as.character(data)
data <- dfm(data, stem = TRUE, remove = stopwords('english'),
            remove_punct = TRUE) %>% dfm_trim(min_termfreq = 2)
out <- convert(data, to = 'stm')

# fit models and effect estimates
gadarian_3 <- stm(documents = out$documents,
                 vocab = out$vocab,
                 data = out$meta,
                 prevalence = ~ treatment + s(pid_rep),
                 K = 3,
                 max.em.its = 1, # reduce computation time for example
                 verbose = FALSE)

prep_3 <- estimateEffect(1:3 ~ treatment + s(pid_rep), gadarian_3,
                       meta = out$meta)

gadarian_5 <- stm(documents = out$documents,
                 vocab = out$vocab,
                 data = out$meta,
                 prevalence = ~ treatment + s(pid_rep),
                 K = 5,
                 max.em.its = 1, # reduce computation time for example
                 verbose = FALSE)

prep_5 <- estimateEffect(1:5 ~ treatment + s(pid_rep), gadarian_5,
                       meta = out$meta)

# save objects in .RData file
save.image(paste0(tempdir(), '/stm_gadarian.RData'))

# launch the app
if(interactive()){
  run_stminsights()
}
```

8

run_stminsights

}

End(Not run)

Index

estimateEffect, [4](#)
exclusivity, [2](#)

get_diag, [2](#)
get_effects, [3](#)
get_network, [5](#)

run_stminsights, [6](#)

semanticCoherence, [2](#)
stm, [2](#)